



A) **Current GDH Pet Wash Pricing** Effective 11/1/10

Premium System \$7,995.00 F.O.B. Plano, TX

Pricing for **Prepaid Shipping** from Plano, TX. to anywhere in the world can be obtained. Once approved by the purchaser, the shipping cost will be added to the unit price of the Pet Wash. The total amount owing is required before the Pet Washes are released for shipping.

B) **Package Includes:**

- 1 – Stainless Steel 48” Tub with Ramp and Back Splash
- 1 – Single Side Access for Better Pet Security
- 1 – Anti Skid Tape Applied to Tub Ramp
- 1 – Tub Strainer
- 1 – Control Panel with 24 Volt Transformer, Circuit Breaker, Terminal Strip and Relay
- 1 – Injection Manifold (Dema Injector with CFA Injection Block)
- 1 – Spray Nozzle Squeeze Trigger
- 1 – **Dryer** Mounted on Control Panel
- 1 – **Extractor** System for Water Removal
- 1 – **Raised Floor Grating**
- 1 – Dryer – Hose 15’ x 1.5” (comes with coupler and hose attachment)
- 1 – Dryer Hose Holder
- 1 – External In-Line Strainer
- 1 – Tempering Valve
- 1 – Water Pressure Control Valve
- 2 – Pet Safety Tie
- 5 – Hose and Foot Valves for Chemicals

Pay Station and Selection Switch Includes:

- 1 – Stainless Steel Hull/Door
- 1 – Coin Acceptor
- 1 – Bill Acceptor
- 1 – LED Display Timer
- 1 – 10 Function Rotary Switch
- 2 – Locks
- 1 – Coin Vault with Door

C) Basic Requirements:

- ½” Hot and Cold water supply
- 1 1/2” connection to a sewer line
- 120V 20A dedicated circuit to the Control Panel
- Recommended size of the Pet Wash area/room - 100 sq. ft.

D) Dimensions Pet Wash Tub:

All Approximate and May Vary

- Length (with the ramp extended) 88”
- Width of Tub 49.5”
- Height of Tub 58”
- Depth of Tub 24”

Additional Space is required for Control Panel and Wash Solutions.

E) Potential Locations for a Self Serve Pet Wash:

- Existing and Proposed Full Serve and Self Serve Car Washes
- Pet Centers, Kennels, SPCA locations and Residential Developments
- Full Service Grooming Centers
- Laundry Facilities
- Marina’s, RV Parks and Truck Stops
- Stand alone SELF SERVE GROOMING CENTERS

F) Self Serve Grooming Room Size & Ideal Location:

We recommend an enclosed and vented room measuring 10' x 10'. We believe the pet and pet owner need a degree of privacy in order to complete the grooming process.

The back of the wash tub should be against a wall to accommodate the power, water and sewer connections with as little exposure as possible. This also provides maximum room for the pet owners while the ramp is extended and resting on the floor. The required control panel is ideally located on the other side of the wall in a utility room.

Locating the Pet Wash room adjacent to a washroom, or the equipment room at a carwash or laundry, should be seriously considered. Each of these rooms requires power and water, while the washroom and Pet Wash require connections to a sewer. Construction and installation costs can be reduced if these three service lines are in close proximity to the Pet Wash.

If a utility room is not available for the control panel and wash solutions, then an optional control panel enclosure is recommended.

G) Wash Room Considerations:

Due to the moisture in the room, materials selected for the walls, ceiling and floor are very important. Not only should they be able to withstand constant contact with varying degrees of moisture, the floor in particular should be able to handle the majority of the moisture, without being slippery. A floor drain would be a good idea. And a non-slip floor mat or covering is recommended also.

Regardless of the geographic location in North America, **the room should be vented to the outside, so airborne moisture and odor can escape.**

A climate controlled wash area is recommended.

H) Services Required:

- 1 - 120V 20A dedicated circuit to the control panel (CP)
- 24 V circuit from the CP to the Coin/Cash Acceptor box
- 24V circuit from the Coin Acceptor box to the Control Panel
- 120V circuit from the CP to the Dryer (hardwire attached dryer cable to (CP)
- ½" hot and cold water service to control panel
- 1 ½" connection from each Pet Wash that will drain into an approved sewer line, not into a storm sewer outlet.

If there is no existing warm water supply the Pet Wash can utilize, then we recommend a 40 gallon hot water tank. This will supply sufficient warm water to ensure that every grooming session has a sufficient supply.

I) Wash Solutions:

GDH offer a complete line of high quality pet cleaning and conditioning solutions. Clearly marked plastic lines, with foot valves attached to the bottom of each line, carry the correct amount of solution when the pet owner chooses a grooming product on the Rotary Switch, ie shampoo, conditioner, de-skunk,

It is recommended the customer use the tub disinfectant before washing their pet. The tub disinfectant should never be used on a pet.

All wash solutions are available on-line at www.carwashstore.com

J) Coin / Cash Acceptor & Digital Display Timer:

The GDH Pet Wash System will accept quarters, \$1 & \$5 bills. It does not make change.

The Digital Display Timer is pre-set in our factory for testing. However, it is easily adjustable to suit the market conditions at your location. **Five dollars for six minutes is a recommended setting for initial use of the Pet Wash**, then a lower amount for fewer minutes to complete the grooming.

The Digital Display Timer will show amount of money accepted, then wash time remaining.

K) Dryer and Extractor:

The dryer motor is completely enclosed and securely mounted to the control panel. It is important to secure the hose when not in use, so it is not on the floor. A stainless steel holder has been provided for this purpose.

The Dryer will be “hard wired” into the Control Panel. If the Control Panel is installed as recommended on the opposite side of the wall from the back of the Pet Wash, installation will be easy. A piece of PVC pipe in the wall will allow the hose to pass through into the Pet Wash room and it should enter the room next to the Coin Box.

The Dryer draws ambient air through the filter at the end of the unit. Caution should be exercised to ensure this area is never blocked. The Dryer may warm the air as it passes through the motor but the air is not heated and equipment room temperature will impact the dryer air temperature. Heated dryer air is not recommended for pets.

Some owners have suggested that **long haired dogs, such as Golden Retrievers, will almost always require a “toweling down” to begin the drying process**. In this regard, towels, plus other pet related products, should be included in a “Pet Related” vending machine easily accessible to Pet Wash customers.

The **Premium System** includes an Extractor System that can be used to remove the access water from a pet before drying. Installation and hose placement for the extractor is similar to the dryer. The Extractor will be mounted on the control panel at the factory next to the dryer. A second stainless steel holder will be provided for the extractor hose.

L) **General:**

Although our Pet Wash is comprised of very straightforward pieces of equipment and the directions are easy to follow, the electrical components may be somewhat complex and might confuse someone who is not a tradesperson. In this regard, **we recommend that a qualified electrician be retained to do the electrical installation** and make the necessary electrical connections between each of the components. Our warranty will not cover any parts that were damaged during the installation.

Similarly, the plumbing requirements are not complex, but, to be on the safe side, **we recommend using a qualified plumber for that portion of the installation.**